



DECLARATION OF PERFORMANCE



No: 11 – DoP – 09/05/2022

305/2011/EU Construction Products Regulation

1) Unique identification code of the product-type

RP-5S / RP-3S / WP-SP / WP-SM / WP-HP / WP-HM / CP-SP

2) Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4)

Polyurethane (PUR) Insulated Sandwich Panels

3) Intended use (according harmonized technical specification) of the product

Metal Surface Insulation Panel for Use in Buildings

DECLARATION OF PERFORMANCE

4) Name, registered trade name and contact address of the manufacturer (In accordance with the fifth paragraph of article 13 of this regulation) :

Teknopanel Çatı ve Cephe Panelleri Üretim San. Ve Tic. A.Ş.

Manisa Turgutlu 1.OSB, Tic. ve San. Odası Bulvarı, 191. Cad. No:19/1, 45400, Selvilitepe, Turgutlu, Manisa

www.teknopanel.com.tr

5) Name and contact address of the authorized representative (As per the second paragraph of Article 14 of this regulation)

Not applicable.

6) System(s) of assessment and verification of constancy of Performance of the construction product (specified in Annex-5 of this regulation)

System 3

7) Case a construction product covered by a harmonized standard:

TSE/ 1783 has been evaluated by the accredited laboratory for the constancy of performance and type tests of the material have been carried out under system 3 based on type calculations, tabulated values or explanatory documents. Based on the test report numbered 2022-62158, a performance statement was drawn up.

8) Case of a construction product for which a European Technical Assessment has been issued

Not applicable.

DECLARATION OF PERFORMANCE

9) DECLARED PERFORMANCE

All characteristics listed in the table hereunder are determined in harmonized standard TS EN 14509:2014

Essential Characteristics	Performance	Harmonized Technical Specification
Shear Strength (fcv)	Min 0,011 Mpa	Mechanical Strength
Shear Modulus (G)	Min. 2 MPa	
Compressive Strength	Min. 0,080 MPa	
Shear Strength After Long-Term Loading (fcv long term) (t=1.000 hours, -t=2.000 hours, -t=100.000 hours)	0,070 Mpa 0,065MPa 0,040MPa	
Creep Coefficient (Φ t=100.000 hours) for Roofs (Snow Load):	Max. 1,8	
Creep Coefficient (Φ t=2.000 hours) for Roofs (Snow Load):	Max. 1,2	
Cross Panel Tensile Strength	Min. 0,050 MPa	
Bending Moment Capacity and Stiffness	Positive: min. 3,2 kNm/m Negative: min. 2 kNm/m	
Wrinkling Strength	Positive min. 75 MPa Negative min. 75 MPa	
Bending Moment Capacity Over a Central Support	Positive: min. 1 kNm/m Negative: min. 1 kNm/m	
Wrinkling Stress Over a Central Support	Positive: min. 140 MPa Negative: min. 95 MPa	
Reaction to Fire Class	B s2 d0	Reaction to Fire Class
Thermal Conductivity of the Core Material (λ)	$\leq 0,024$ W/mK	Thermal Conductivity
External Fire Performance (For Roof)	BROOF(t1)	External Fire Performance
Water Permeability	NPD	
Air Permeability	NPD	
Water Vapor Permeability	NPD	
Airborne Sound Insulation	NPD	
Sound Absorption	NPD	
Panel Thickness	± 2 mm	
Deviation from Flatness	L=200 mm 0,6 mm L=400 mm 1,0 mm L>700 mm 1,5 mm	Dimensional Variation
Length of Panel (L)	L \leq 3000 mm ± 5 mm L>3000 mm ± 10 mm	
Cover Width (w)	1000 ± 2 mm	
Deviation from Straightness	± 1 mm/m, max. 5 mm	
Deviation from Squareness (s)	$s \leq 0,6\% * w$	

DECLARATION OF PERFORMANCE

The construction material, which is identified above has the declared performance.
This declaration of performance is issued under the responsibility of Teknpanel Çatı ve
Cephe Panelleri Üretim San. ve A.Ş.

Signed for and on behalf of the manufacturer by : Orhan Kahveci

General Manager



Teknpanel Çatı ve Cephe Panelleri Üretim San. ve Tic. A.Ş.
Mrk.: Mersin - Tarsus OSB 7. Cadde No: 10 Akdeniz - Mersin
Tel. : 0324 676 47 47 (pbx) Faks: 0324 676 47 48
ULUSLARARASI V.D: 8360357308 Mersis No: 3459 2712 9664 1458 / 7